

Albi Maxi Adjustable

DOWNLIGHT | Product code MD31

MONDOLUX™
mondolux.com.au






Smart, striking design

- Part of the Albi family
- Great adjustability with maximum tilt angle up to 15°
- Standard SDCM: 3 steps, available in 2 steps on request
- Fixed and adjustable recessed installations both available

Product info

System Lumen Range	675lm — 1830lm
System Power	7W, 13W, 18W
Forward Current	180mA, 350mA, 500mA
System Efficacy (max.)	102lm/W
Body/Trim Colour	White, Black
Installation Method	Adjustable Recessed
LED Brand	CREE, Bridgelux
Dimming Type	Phase-Cut Dimmable, Wireless Dimmable (Casambi), Non-Dimmable, DALI Dimmable
Accessories	Without Accessory, Deep Baffle + Diamond Diffuser, Deep Baffle + Frosted Diffuser, Deep Baffle + IP44 Diffuser, Deep Baffle + Line Diffuser, Diamond Diffuser, Frosted Diffuser, Honeycomb Louvre, IP44 Diffuser, Line Diffuser



Photometric info

Colour Rendering Index (CRI)	CRI90, CRI97+
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim To Warm
Beam Angle	15°, 30°, 50°

Albi Maxi Adjustable

DOWNLIGHT | Product code MD31

Compliance and Features




Packaging


Box Dimensions L x W x H mm	110 mm x 110 mm x 200 mm
Boxes per Carton	24
Carton Weight	12 KG
Carton Dimensions L x W x H mm	450 mm x 340 mm x 410 mm

Polar distribution diagrams

*Albi 7W/13W/18W 15°



*Albi 7W/13W/18W 30°



*Albi 7W/13W/18W 50°

