






## Architectural design with impressive glare control

- Sleek architectural downlight
- Improved luminous efficiency with new Cross Beam Lens
- Minimised glare with deep recessed round pinhole
- Excellent beam control

### Product info

System Lumen Range	675lm — 1830lm
System Power	7W, 13W, 18W
Forward Current	180mA, 350mA, 500mA
System Efficacy (max.)	102lm/W
Body/Trim Colour	White, Black
Installation Method	Adjustable Recessed
LED Brand	CREE, Bridgelux
Dimming Type	Phase-Cut Dimmable, Wireless Dimmable (Casambi), Non-Dimmable, DALI Dimmable
Accessories	Without Accessory, Deep Baffle + Diamond Diffuser, Deep Baffle + Frosted Diffuser, Deep Baffle + IP44 Diffuser, Deep Baffle + Line Diffuser, Diamond Diffuser, Frosted Diffuser, Honeycomb Louvre, IP44 Diffuser, Line Diffuser



### Photometric info

Colour Rendering Index (CRI)	CRI90, CRI97+
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim To Warm
Beam Angle	15°, 30°, 50°

## Compliance and Features



## Packaging

Box Dimensions L x W x H mm	110 mm x 110 mm x 200 mm
Boxes per Carton	24
Carton Weight	12 KG
Carton Dimensions L x W x H mm	450 mm x 340 mm x 410 mm

## Polar distribution diagrams

