



Infinito

Downlight







About Mondolux

Mondolux is an innovative lighting brand developed by Aglo Systems. The Mondolux brand showcases on-trend lighting products with the latest technology and guaranteed quality to make the entire process clear and simple. Our promise is to continually improve our clients' lighting experience.

Quick Turnaround Times

With a stocked warehouse of 3000 sqm and an experienced assembly team in Melbourne, we are able to fulfil your orders quickly.

Technical Data

Clear technical drawings, detailed product photos, illumination diagrams, IES files and installation instructions are some of the downloadable resources we have available for all our products.

Comprehensive Catalogue

We understand the need to use several variations of

a fitting in a space to meet the desired interior architecture and illumination needs. We offer a wide range of products available in many sizes, lumen outputs, beam angles, accessories and colour temperatures.

Easy Product Search and Selection

Our website is a platform which enables users to find the perfect lighting solution in a quick and easy way. The user can select the different features of the required lighting product and quickly identify all products that meet these specifications and have the required technical data at their fingertips.


Guaranteed Quality Product

Our products are thoroughly tested, warranted and certified to meet Australian, New Zealand and European compliance standards.


Infinito Series

The Infinito modular series is an architectural downlight range that offers a wide variety of product combinations. The broad range of models and accessories provide an array of options to create ambience in architectural developments.

The Infinito series uses the latest in optical technology to further maximise light output while maintaining performance. The new, high efficiency Cross Beam Lens shifts the focus away from the lens surface itself, reducing glare and minimising luminaire cut-off losses. Most beneficial when the source light is used with a deep baffle light fixture such as Albi Round/Oval Pinhole.



STANDARD LENS



CROSS BEAM LENS

Key Features:

- Modular design
- Serviceable from the front*
- Cross Beam lens
- Beam Angles: 15°, 30°, 50°
- Colour Temperature (CCT): 2700K, 3000K, 4000K, Dim to Warm
- Colour Rendering Index (CRI): CRI90, CRI97 available upon request
- Standard Deviations of Colour Matching (SDCM): 3-step as standard, 2-step available on request
- Accessories: Honeycomb Louvre, Line Diffuser, Diamond Diffuser, Frosted Diffuser, IP44 Diffuser, Deep Baffle
- Dimmable Options: Phase-Cut, DALI, Casambi Wireless
- Module Power: 7W, 13W, 18W



*Applicable for Bron and Malo range only

**Applicable for Albi Mini Fixed - IP fitting only





Infinito Series

Bron

Module



7W



13W



18W

Accessory



Honeycomb Louvre



Line Diffuser



Diamond Diffuser



Frosted Diffuser



IP44 Diffuser



Deep Baffle

Baffle



Round White



Round Black



Round Rose Gold




Round Chrome




Square White



Square Black



Square Rose Gold



Square Chrome

Trim



Round



Trimless Round



Adjustable




Square




Trimless Square

Bron


MD40FR Bron Fixed



Trim colour	White, Black, Custom
Lumen Output	675lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°




Trim colour	White, Black, Custom
Lumen Output	1375lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°




Trim colour	White, Black, Custom
Lumen Output	1830lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°


MD40TF Bron Fixed Trimless



Trim colour	White, Black, Custom
Lumen Output	675lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°



Trim colour	White, Black, Custom
Lumen Output	1375lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°




Trim colour	White, Black, Custom
Lumen Output	1830lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°


Infinito Series

Bron


MD41FR
Bron Square Fixed



Trim colour	White, Black, Custom
Lumen Output	675lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°





Trim colour	White, Black, Custom
Lumen Output	1375lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°




Trim colour	White, Black, Custom
Lumen Output	1830lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°


MD41TF
Bron Square Fixed
Trimless



Trim colour	White, Black, Custom
Lumen Output	675lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°




Trim colour	White, Black, Custom
Lumen Output	1375lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°




Trim colour	White, Black, Custom
Lumen Output	1830lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°

Bron


MD40AR Bron Adjustable



7W



13W



18W


Trim colour	White, Black, Custom
Lumen Output	675lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°

Trim colour	White, Black, Custom
Lumen Output	1375lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°


Trim colour	White, Black, Custom
Lumen Output	1830lm (up to)
Baffle Colour	White, Black, Rose Gold, Chrome
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°

Photometric Information


7W/13W/18W Module only 15°



7W/13W/18W Module only 30°



7W/13W/18W Module only 50°



Images depict generic values. For specific module data, visit www.mondolux.com to download the IES file.

Code Information

Family Code +	Product +	Installation Type +	Trim Colour +	Beam Angle +	CRI +	CCT +	Power & Current +	Dimming Options +	Baffle +	Accessories +
MD = Mondolux Infinito Downlight	40 = Bron	FR = Fixed Recessed	1 = White	S = 15°	9 = CRI90	27 = 2700K	018A = 180mA, 7W	0 = Non-Dimmable	WB = White Baffle	HC = Honeycomb Louvre
	41 = Bron Square	TF = Trimless Fixed Recessed	2 = Black	M = 30°	H = CRI97	30 = 3000K	035A = 350mA, 13W	2 = Phase-cut Dimmable	BB = Black Baffle	LD = Line Diffuser
		AR = Adjusted Recessed	9 = Custom	W = 50°		40 = 4000K	050A = 500mA, 18W	3 = DALI Dimmable	RG = Rose Gold Baffle	DD = Diamond Diffuser
						DW = Dim to Warm		6 = Casambi Dimmable	CB = Chrome Baffle	FD = Frosted Diffuser
										IP44 = IP44 Diffuser
										DB = Deep Baffle

Example:

MD41TF2S-927-050A0-GB-HC

Mondolux Infinito Downlight Bron Square Trimless Fixed Recessed Black 15° X-Beam CRI90 2700K 1630lm 18W 500mA Non-Dimmable C/W Rose Gold Baffle and Honeycomb Louvre



Albi

Module



7W



13W



18W

Accessory



Honeycomb Louvre



Line Diffuser



Diamond Diffuser



Frosted Diffuser



IP44 Diffuser



Deep Baffle

Trim



Mini Fixed



Mini Fixed IP



Mini Adjustable



Maxi Fixed



Maxi Adjustable



Round Pinhole




Oval Pinhole

Infinito Series


Albi

MD33
Albi Oval Pinhole




7W

Trim colour	White, Black, Custom
Lumen Output	675lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°



13W


Trim colour	White, Black, Custom
Lumen Output	1375lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°



18W


Trim colour	White, Black, Custom
Lumen Output	1830lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°

MD32
Albi Round Pinhole




7W

Trim colour	White, Black, Custom
Lumen Output	675lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°



13W

Trim colour	White, Black, Custom
Lumen Output	1375lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°




18W


Trim colour	White, Black, Custom
Lumen Output	1830lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°

Albi


MD34FR
Albi Mini Fixed - IP54



7W



13W



18W




Trim colour	White, Black, Custom
Lumen Output	675lm (up to)
Baffle Colour	White
IP Rating	IP54
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°


Trim colour	White, Black, Custom
Lumen Output	1375lm (up to)
Baffle Colour	White
IP Rating	IP54
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°

Trim colour	White, Black, Custom
Lumen Output	1830lm (up to)
Baffle Colour	White
IP Rating	IP54
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°


MD31FR
Albi Maxi Fixed



7W



13W



18W



Trim colour	White, Black, Custom
Lumen Output	675lm (up to)
Baffle Colour	White
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°


Trim colour	White, Black, Custom
Lumen Output	1375lm (up to)
Baffle Colour	White
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°

Trim colour	White, Black, Custom
Lumen Output	1830lm (up to)
Baffle Colour	White
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°

Infinito Series


Albi

MD31AR
Albi Maxi Adjustable




7W

Trim colour	White, Black, Custom
Lumen Output	675lm (up to)
Baffle Colour	White
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°



13W


Trim colour	White, Black, Custom
Lumen Output	1375lm (up to)
Baffle Colour	White
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°



18W


Trim colour	White, Black, Custom
Lumen Output	1830lm (up to)
Baffle Colour	White
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°

MD30AR
Albi Mini Adjustable




7W

Trim colour	White, Black, Custom
Lumen Output	675lm (up to)
Baffle Colour	White
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°



13W

Trim colour	White, Black, Custom
Lumen Output	1375lm (up to)
Baffle Colour	White
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°




18W


Trim colour	White, Black, Custom
Lumen Output	1830lm (up to)
Baffle Colour	White
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°

Albi


MD30FR
Albi Mini Fixed



7W



13W



18W




Trim colour	White, Black, Custom
Lumen Output	675lm (up to)
Baffle Colour	White
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°

Trim colour	White, Black, Custom
Lumen Output	1375lm (up to)
Baffle Colour	White
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°


Trim colour	White, Black, Custom
Lumen Output	1830lm (up to)
Baffle Colour	White
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°

Photometric Information


7W/13W/18W Module only 15°



7W/13W/18W Module only 30°



7W/13W/18W Module only 50°



Images depict generic values. For specific module data, visit www.mondolux.com to download the IES file.

Code Information

Family Code +	Product +	Installation Type +	Trim Colour +	Beam Angle +	CRI +	CCT +	Power & Current +	Dimming Options +	Accessories +
MD = Mondolux Infito Downlight	30 = Albi Mini	FR = Fixed Recessed	1 = White	S = 15°	9 = CRI90	27 = 2700K	018A = 180mA, 7W	0 = Non-Dimmable	HC = Honeycomb Louvre
	31 = Albi Maxi	AR = Adjustable Recessed	2 = Black	M = 30°	H = CRI97	30 = 3000K	035A = 350mA, 13W	2 = Phase-cut Dimmable	LD = Line Diffuser
	32 = Albi Oval Pinhole		9 = Custom	W = 50°		40 = 4000K	050A = 500mA, 18W	3 = DALI Dimmable	DD = Diamond Diffuser
	33 = Albi Round Pinhole						DW = Dim to Warm	6 = Casambi Dimmable	FD = Frosted Diffuser
	34 = Albi Mini IP54								IP44 = IP44 Diffuser
									DB = Deep Baffle

Example:

MD30FR1S-927-035A0-IP54

Mondolux Infito Downlight Albi Mini Fixed Recessed White IP54 15° X-Beam CRI90 2700K 1390lm 13W 350mA Non-Dimmable



Malo

Module



7W



13W



18W

Accessory



Honeycomb Louvre



Line Diffuser



Diamond Diffuser



Frosted Diffuser



IP44 Diffuser



Deep Baffle

Trim



Adjustable



Trimless



Duo Adjustable





Duo Trimless

Infinito Series


Malo

MD45AR
Malo Uno




7W

Trim colour	White, Black, Custom
Lumen Output	675lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°



13W


Trim colour	White, Black, Custom
Lumen Output	1375lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°



18W


Trim colour	White, Black, Custom
Lumen Output	1830lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°

MD45TA
Malo Trimless




7W

Trim colour	White, Black, Custom
Lumen Output	675lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°



13W

Trim colour	White, Black, Custom
Lumen Output	1375lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°




18W

Trim colour	White, Black, Custom
Lumen Output	1830lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°


Malo

MD46AR Malo Duo




2 x 7W

Trim colour	White, Black, Custom
Lumen Output	2 x 675lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°



2 x 13W


Trim colour	White, Black, Custom
Lumen Output	2 x 1375lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°



2 x 18W


Trim colour	White, Black, Custom
Lumen Output	2 x 1830lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°

MD46TA Malo Duo Trimless




2 x 7W

Trim colour	White, Black, Custom
Lumen Output	2 x 675lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°



2 x 13W

Trim colour	White, Black, Custom
Lumen Output	2 x 1375lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°




2 x 18W

Trim colour	White, Black, Custom
Lumen Output	2 x 1830lm (up to)
Baffle Colour	White, Black
Colour Rendering Index (CRI)	CRI90, CRI97
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim to Warm
Beam Angle	15°, 30°, 50°


Infinito Series

Photometric Information


7W/13W/18W Module only 15°



7W/13W/18W Module only 30°



7W/13W/18W Module only 50°



Images depict generic values. For specific module data, visit www.mondolux.com to download the IES file.



Code Information

Family Code +	Product +	Installation Type +	Trim Colour +	Beam Angle +	CRI +	CCT +	Power & Current +	Dimming Options +	Accessories +
MD = Mondolux Infinito Downlight	45 = Malo Uno	AR = Adjustable Recessed	1 = White	S = 15°	9 = CRI90	27 = 2700K	018A = 180mA, 7W	0 = Non-Dimmable	HC = Honeycomb Louvre
	46 = Malo Duo	TA = Trimless Adjustable Recessed	2 = Black	M = 30°	H = CRI97	30 = 3000K	035A = 350mA, 13W	2 = Phase-cut Dimmable	LD = Line Diffuser
			9 = Custom	W = 50°		40 = 4000K	050A = 500mA, 18W	3 = DALI Dimmable	DD = Diamond Diffuser
						DW = Dim to Warm		6 = Casambi Dimmable	FD = Frosted Diffuser
									IP44 = IP44 Diffuser
									DB = Deep Baffle

Example:
MD46AR1W-927-035A0-HC
Mondolux Infinito Downlight Malo Duo Adjustable Recessed White 50° X-Beam CRI90 2700K 2x 1390lm 2x 13W 350mA Non-Dimmable C/W Honeycomb Louvre







MONDOLUX™

- T** 1300 601 931
- E** contact@mondolux.com
- W** mondolux.com

Distributed by

aglo
SYSTEMS™

- W** aglosystems.com.au